[http://www.cartft.com/catalog/il/1313]





999.00 EUR

incl. 19% VAT, plus shipping

- 2x RS232!
- USB Host!
- Dual Core 900Mhz!
- 256MB RAM!

Support: RS232 Pinout | WinCE Mode | GUI GPS Link | Rear camera sensor | RS232 Pinout (CMO-Version) | SDK | Developer Notes

The CTFPND-6 is a 7" Touchscreen PND on Windows CE 6.0 basis with integrated GPS receiver and RS232 interfaces. Therefor the CTFPND-6 is the perfect plattform for your telematics application. The extra-high native resolution of 800x480 enables a perfect viewing quality.

The device is equipped with a FM transmitter,2x RS232, USB Host and video input. Optionally this device can be equipped with an external TMC receiver.

Note: This PND is an offer primarily meant for business and project customers. End consumers should only consider purchasing this device when they have appropriate experience.

Hardware

CPU Flash ROM SDRAM TFT LCD Resolution Prima Dual Core 900Mhz 128MB NAND Flash (BGS type) 256 MB DDR-II 7" Touchscreen (Samsung, 24bit color) 800x480



[CTFPND-6] 7" PND (2x RS232, USB-Host, FM, AV-IN, 800x480, 900Mhz, 256MB RAM) [Minimum order qty. 250 units]

[http://www.cartft.com/catalog/il/1313]

TMC

RS232

FM Transmitter

Speaker

Memory slot

GPS

Video Input

Connector

Power
Weight
Dimensions
Software

Operating system

Navigation software

Features

Lieferumfang



Optional

2x Integrated (TTL or 12V depending on adapter cable)

Integrated Integrated

SD/SDHC (up to 32GB, SanDisk recommended)

Integrated, SIRFstar III (20 channels)

2 AV inputs (Rear CAM support)

- SD extension box (optional)
- 2x Serial port
- USB slave
- Rear camera (3.55mm jack)
- AV-In (3.55mm jack)
- SD slot
- External IR (optional)
- USB Host
- Power socket DC
- 3.55mm stereo earphone jack
- Antenna socket for external GPS antenna (additional antenna not included)

12/24V DC (1.5A PMIC, Rebooting protection circuit)

368g

190 x 120 x 20 mm

MS Windows CE.NET 6.0 (core version)

Optional

- Generic RNDIS driver (installed)
- Compact .NET Framework 3.5 (installed)
- CTFPND-6 (7" PND)
- Mounting adapter
- 12/24V cigarette lighter adapter
- AC/DC-adapter
- 2x RS232 cable (TTL + 12V) [12V power source not included]
- Window suction mounting unit