[http://www.cartft.com/catalog/il/1382]



999.00 EUR

incl. 19% VAT, plus shipping

- Fanless!
- Auto Power On/Off!
- CAN-BUS 2.0B
- 3x RS232!



Support: Device Specification | CAN-BUS Manual [EN] | Manual [EN] | Drivers (Windows) | Internal GPS Module |
Drivers (CAN-BUS) | Drivers (GPS)

This MiniPC was especially designed for fleet applications. The Car-PC can be connected directly to the car battery (12V/24V). Based on ignition plus, the PC will start and shutdown.

For a full PC you need in addition:

- 2.5" HDD/SSD or CompactFlash

The PC is completely fanless and is equipped with an AMD G-T56N 2x1.6GHz CPU.

## Available additional modules:

The PC comes with 4x antenna-output and 3x Mini-PCle slots.

We recommend these modules:

- HSPA / UMTS / EDGE Mini-PCIe Modem (Huawei EM770W)
- Wireless LAN / Bluetooth Mini-PCI Express [Qcom Combo]

## Features:

- Fanless
- AMD G-T56N Dual Core CPU
- AMD Radeon HD 6320 Graphics
- GPS (Atheros Chipsatz)
- 1x CAN BUS 2.0B
- 3x RS232
- 2x Gigabit LAN
- DVI-I + DSUB-15 VGA



## FleetPC-5 Car-PC (AMD G-T56N 2x1.65Ghz, Autostart-Controller, 9-36V Automotive PSU, GPS, CAN-BUS) [FANLESS]

[http://www.cartft.com/catalog/il/1382]

- Watchdog
- Prepared for GPS, WLAN, GSM/GPRS with ext. antennas
- 2 x DI / 2 x DO with Relay 12V / 100mA
- Vibration/shock tested

For FleetPC-5 we offer an direct connector cable for our TFT-dispays.

Dimensions / Weight

CPU

Chipset / FSB

RAM Graphics GPS

Expansion OS Support

Vibration & Shock
Operating temperature

Certification

I/O

Drive bays

Power supply

Scope of supply

235mm W x 155mm D x 55mm H, 1.5kg AMD G-T56N Dual Core 2x 1.65GHz

AMD A55E Controller Hub

2x SO-DDR-3 RAM (up to 8GB 1333Mhz)

AMD Radeon HD 6320 Locosys LS26050

- 3x Mini-PCle

Windows XP Home/Pro/Embedded, Windows 7/8, Linux

MIL-STD-810F -30~60°C (with SSD)

CE, FCC, eMark (2009/19/EC, CISPR 25:2008, ISO 7637-2:2004),

Railway EN50155

- 2x Gigabit LAN (Realtek RTL8111E)
- 3x RS232 (2x with RS-422/485)
- 4x USB2.0
- GPIO port (2in, 2out, with Relay 12V/100mA)
- SPK Out
- 1x DVI + 1x DSUB-15 VGA
- 4x SMA Antenna hole (for eg. GPS, GSM/GPRS/3G, WLAN,

Bluetooth)

1 x 2.5" SATA HDD/SSD drive bay

9~32V DC PSU included

- Power off Delay Time Setting by Software, Default 5min
- Backup Battery Kit (optional)
- FleetPC-5 PC with AMD G-T56N (2x1.6Ghz), mounting
- 1x Pigtail + antenna for GPS