



798.00 EUR

incl. 19% VAT, plus shipping

- -25 °C to 70 °C
- 3x Intel 82574L Gigabit
- 4x COM

Support: 1 Specifications [EN]

Boosting your computing engine to a new era! Incorporating Intel Core[™] i7/i5 processor, the Nuvo-1000 controller offers extraordinary performance for arithmetic-intensive applications, while its fanless embedded design provides superb reliability and durability. The system comes with unique and smart main board and mechanical design. It is formed up only by a single main board and single heat sink to achieve most ruggedized and widest operating temperature embedded system in the market.

Nuvo-1000 also integrates versatile I/O interfaces in a compact chassis. It provides up to 5 Gigabit Ethernet ports and 2 eSATA ports, which is particularly useful for machine vision, surveillance and security applications. The VGA+DVI/HDMI dual display accomplishes an easy way of high-resolution content output for image or media applications. In addition, Nuvo-1000 also features rich IO functions, such as optional isolated DIO and PCI-104 expansion bus, to fit a broader range of applications.

The fanless design of Nuvo-1000 gives it exceptional long-term durability and tolerance to vibration, and its -25°C to +70°C temperature range provides a more reliable operation in various environments. For a quest of performance and reliability, Nuvo-1000 is the answer!

For a full PC you need in addition :



- Intel Core i5/i7 Mobile CPU (PGA-988)

- SO-DDR-III RAM

- 2.5" HDD/SSD or CompactFlash

System Core Intel Core i3, i5, i7 mobile processors Processor Socket G (rPGA988A) [i7-620M,i5-540M,i5-520M,i5-450M,i5-430M] Intel® HM55 Platform Controller Hub Chipset Graphics Integrated Intel® HD Graphics Controller Memory 1x 204-pin SO-DIMM socket, up to 4GB DDR3 1066MHz SDRAM Front-panel I/O Interface Ethernet 1x Intel® 82574L Gigabit Ethernet port 1x DB-15 connector for analog RGB, supporting 2560x1600 resolution Video Port 1x DVI-D connector for DVI/HDMI output, supporting 1920x1080 resolution 1x software-programmable RS-232/422/485 (COM1) Serial Port 3x RS-232 (COM2 ~ COM4) USB 6x USB 2.0 ports KB/MS 1x PS/2 keyboard and 1x PS/2 mouse Audio 1x Mic-in and 1x Speaker-out Digital I/O 8x isolated DI and 8x isolated DO (optional) Storage Interface SATA HDD 1x Internal SATA port for 2.5" HDD/SSD installation eSATA 2x eSATA ports for storage expansion CompactFlash 1x Type I CF socket Expansion Bus Mini PCI-E 1x internal mini PCI Express socket with SIM socket PCI-104 1x Internal PCI-104 socket (optional) **Power Supply** DC Input Built-in 8~28 VDC DC input 1x 4-pin pluggable terminal block with remote on/off control Input Connector 1x DC jack (ø2.5) for AC/DC adapter input Mechanical Dimension 240 mm (W) x 195 mm (D) x 76 mm (H) Weight 2.7 Kg (including 2.5" HDD and DDR3 SODIMM) Mounting Wall-mount by mounting bracket Environmental Ambient with air flow (> 0.5 m/s or 1.8 km/hr), 100% CPU loading* -25°C ~ 70°C (Nuvo-1005S-620M & Nuvo-1003S-520M) -25°C ~ 60°C (Nuvo-1003S-4500P) Ambient without air flow, 100% CPU loading* **Operating Temperature** -25°C ~ 60°C (Nuvo-1005S-620M & Nuvo-1003S-520M) -25°C ~ 50°C (Nuvo-1003S-4500P) -40°C extended temperature option is also available. Please contact Neousys for further information. StorageTemperature -40°C ~ 85°C Humidity 10%~90%, non-condensing Operating, 5 Grms, 5-500 Hz, 3 Axes Vibration (w/ SSD, according to IEC60068-2-64) Operating, 50 Grms, Half-sine 11 ms Duration Shcok (w/ SSD, according to IEC60068-2-27) EMC CE/FCC Class A, according to EN 55022 & EN 55024



