

919.00 EUR
incl. 19% VAT, plus [shipping](#)



- INTEL® BayTrail--M N2930 SOC
- Onboard INTEL® BayTrail-M N2930 1.83GHz Quad Cores CPU
- Onboard SAMSUNG 4G/1333MHz DDR3L Memory
- Support DirectX 11 3D Graphics Acceleration
- Support 1*Serial ATAll(3Gb/s) Devices
- Support Dual INTEL® Gigabit LAN
- Support CRT Output
- Equipped with 802.11 b/g/n WIFI card & External Antenna
- Support 3* COM ports■COM2/COM3 Support RS422/485■
- Support 2.5" SATA HDD
- Support 1*M-SATA Socket
- Support 1*Mini PCI-E Socket
- Support 3* USB2.0 Ports
- Support 1* USB3.0 Port
- Support 3G SIM Card
- 37mm thin, slice design
- VESA mount(100mm X100mm &75mm x 75mm)

Panel	Panel Spec	AUO G121XN01.V0
	Viewable Size Image	12.1 inch With LED Backlight
	Active Area	245.76(H) x 184.32(V)
	Resolution	1024 x 768 @60Hz
	Display Color	262K
	Pixel Pitch	0.24 x 0.24 mm
	Aspect Ratio	4:3
	Contrast Ratio	700:1
	Max Brightness	500 cd/m ²
	Viewing Angle(H/V)	H160/V160
	Response Time	25ms
	Temperature Range	-30 ~ +80°C (Operating)
Touch	Touch panel style	5 wires analog resistive
	Active Range	249.80 x 188.50mm ±0.2mm
	Temperature Range	-10 ~ +60°C (Operating)
	Transparency	80 ±3%
	Surface Hardness	■ 3H (ASTM D3363, pressure 750g/45°)
	Operating Force	■ 80g
	Knock test	10,000,000 times keystrokes