

649.00 EUR

incl. 19% VAT, plus [shipping](#)

- JBC390F541CA-19-B



- Intel® Bay Trail SoC Processor
- 1 * SO-DIMM DDR3L 1333MHz up to 8GB
- 3 * USB2.0, 1 * USB3.0, 1 * COM, 1 * VGA, 1 * HDMI, 2 * RJ45, 1 * MIC, 1 * Line out
- Product Dimension : 185 x 165 x 48 mm
- DC-12V_5A_60W Lockable Adapter

| | | | | | | |
|---------------------------------|---|---------------------------------|------------------------------------|---------------------------------|---------------------------------|---------------------------------|
| MB Model | - JNF541-1900 | | | | | |
| Part No | No Expansion | 8 LAN | 8 COM | 16-bits GPIO | 32-bits GPIO | 4 USB 3.0 |
| | - | - | - | - | - | - |
| | HBJC390F541XX-1900-B | HBJC390F541AA-1900-B | HBJC390F541CC-1900-B (non-WIFI) | HBJC390F541XG-1900-B | HBJC390F541GG-1900-B | HBJC390F541XU-1900-B |
| | - | - | - | - | - | - |
| | HBJC390F541WXX-1900-B (Wifi) | HBJC390F541WAA-1900-B (Wifi) | HBJC390F541WCC-1900-B (Wifi) | HBJC390F541WXG-1900-B (Wifi) | HBJC390F541WGG-1900-B (Wifi) | HBJC390F541WXU-1900-B (Wifi) |
| | 4 COM+4 LAN | 4 COM+4 USB3.0 | 4 LAN+4 USB3.0 | 4 COM+16-bits GPIO | 4 LAN+16-bits GPIO | 16-bits GPIO+4 USB 3.0 |
| - | - | - | - | - | - | |
| HBJC390F541CA-1900-B | HBJC390F541CU-1900-B | HBJC390F541AU-1900-B | HBJC390F541CG-1900-B | HBJC390F541AG-1900-B | HBJC390F541GU-1900-B | |
| - | - | - | - | - | - | |
| HBJC390F541WCA-1900-B (Wifi) | HBJC390F541WCU-1900-B (Wifi) | HBJC390F541WAU-1900-B (Wifi) | HBJC390F541WCG-1900-B (Wifi) | HBJC390F541WAG-1900-B (Wifi) | HBJC390F541WGU-1900-B (Wifi) | |
| BIOS | - AMI EFI Flash ROM | | | | | |
| CPU/Chipset | - Intel® Bay Trail J1900 SoC Processor | | | | | |
| Memory | - 1 * DDR3L-1066/1333 SO-DIMM up to 8GB | | | | | |
| Storage | - 1 * 2.5" SATA drive bay (only support 2.5" HDD with a height ≤ 10mm) - 1 * Full-size mSATA/Mini-PCI Express shared slot | | | | | |
| Network | - 2 * Intel i211AT Gigabit LAN - 1 * Half-size Mini-PCIe slot (802.11 b/g/n + BT 4.0 installed in WiFi model) - 1 * SIM Card Slot | | | | | |

| | |
|-----------------|--|
| Rear Panel I/O | <ul style="list-style-type: none"> - 1 * USB 3.0, 3 * USB 2.0 - 1 * HDMI, 1 * VGA - 2 * RJ45 - 1 * Line-out, 1 * MIC-in - 1 * COM (Support RS232/422/485) - 2 * Antenna holes (WiFi only) - Lockable DC-In jack |
| Front Panel I/O | <ul style="list-style-type: none"> - 1 * Power button + LED - 1 * HDD LED - COM (Expansion Module) - Intel Gigabit LAN (Expansion Module, support RS232/422/485) - USB3.0 (Expansion Module) - 16-Bits GPIO (Expansion Module) |
| Power Source | <ul style="list-style-type: none"> - 60W AC-DC Adapter / DC12V-5A - AC 90~240V input |
| Compliance | <ul style="list-style-type: none"> - CE, FCC, RoHS, ErP Ready |
| Temperature | <ul style="list-style-type: none"> - Operating temperature: 0 ~ 50° C - Storage Temperature: -10 ~ 70° C |
| Dimensions | <ul style="list-style-type: none"> - 185 (W) x 165 (D) x 48 (H) mm |
| Packing | <ul style="list-style-type: none"> - Net Weight: 2.4KG - Gross Weight: 3.4KG - Color Box dimension: 250 (W) * 118 (D) * 295 (H) mm |
| OS Support | <ul style="list-style-type: none"> - Windows 7, Windows 8.1, Windows 10, Linux |
| Warranty | <ul style="list-style-type: none"> - 2 Years limited warranty |